
COMMERCIAL GAS THERMOSTATS

 $4200_{\,\text{(FD) BODY TYPE }\#1}$

All FD controls on this page have a Type #1 body.





UNI-LINE ORDER NO.	MODEL TYPE	INLET		OUTLET					
		SIDE "F"	REAR "H"	SIDE "E"	REAR "G"	PILOT OUTLET	CAPILLARY LENGTH	MOUNTING POSITION	BULB SIZE
100 TO 200°F - A	A 3/8" PIPE S1	TUFFING BOX	(IS ATTACE	HED TO CA	PILLARY				
4200-105	FDL	1/2" PIPE		1/2" PIPE		SIDE	36"	UP	3/8" X 6" NICKEL
100 TO 450°F – I	NO DIAL								
4200-401	FDS	3/8" PIPE	3/8" PIPE	3/8" PIPE		REAR	30"	UP	3/8" X 3-1/2" NICKEL
150 TO 550°F									
4200-002	- FDO		7/16" TUBE		7/16" TUBE	NONE	48" 72" 54"	4-WAY	3/16" X 14-3/4 NICKEL
4200-006		1/2" PIPE		1/2"		NONE			1/4" X 8-7/16
4200-007		1/2 11 [PIPE		SIDE			NICKEL
4200-012			7/16" TUBE		7/16" TUBE	NONE			
4200-017	FDTO	1/2" PIPE		1/2" PIPE		SIDE			3/16" X 14-3/4 NICKEL
4200-018						NONE	72"		
4200-025 UNI-KIT	FDO	3/8" PIPE	3/8" PIPE	3/8" PIPE	3/8" PIPE	SIDE & REAR	54"		
200 TO 400°F – I	FRYER APPLIC	CATIONS - BO	OTH MODE	LS HAVE A	3/8" PIPE S	STUFFING E	вох		
4200-701	- FDL	3/8" PIPE		3/8" PIPE		SIDE	36"	UP	5/16" X 9-1/8' NICKEL
4200-702		1/2" PIPE		1/2" PIPE					
LOW (200°F) TO	550°F								
4200-026 UNI-KIT	FDTO	3/8" PIPE	3/8" PIPE	3/8" PIPE	3/8" PIPE	SIDE & REAR	54"	4-WAY	3/16" X 14-3/4 NICKEL
300 TO 650°F	_								
4200-503	FDTH	1/2" PIPE		1/2" PIPE			54"	4-WAY	3/16" X 15-3/8 NICKEL
4200-510 UNI-KIT	FDTH	3/8" PIPE	3/8" PIPE	3/8" PIPE	3/8" PIPE	SIDE			
4200-514	FDH	1/2" PIPE		1/2" PIPE					