

Commercial Electric Thermostats, cont'd

5300 DIRECT REPLACEMENTS (cont.)

Uni-Line Part No.	Dial Temp. Range In °F	Cap. Lgth.	Bulb Size & Finish	Stem Length	Mtg. Brkt Type/Dim.	Dial Type Incl.	Stem Flat Position	Mech. Diff.	Factory No.	OEM & Part No. Comments
5300-673	200 to 850	72"	1/8" x 8-1/4" Stainless Steel	2" Kit	#6, Kit	4-Way	Down	12	KNP-8	1-10 Dial Uni-Kit
5300-507	250 to 800	24"	3/16" x 8-3/4" Stainless Steel	15/16"	#1, 1-3/4"	4-Way	Down	25	KN-1	McGraw-Edison 20A2S-39
5300-514	250 to 850	48"	1/8" x 8-1/4" Stainless Steel	15/16"	#1, 1-3/4"	4-Way	Right	25	KNP-13	Toastmaster 300-4281
5300-671	300 to 700	60"	3/16" x 12-1/4" Nickel	2" Kit	#6, Kit	4-Way	Down	12	SP-200	Uni-Kit
5300-513	300 to 800	72"	3/16" x 12-1/4" Nickel	13/16"	#1, 1-3/4"	4-Way	Right	12	SP-174	F.S. Lang 30402-10
5300-502	250 to 950	36"	5/32" x 8-1/4" Stainless Steel	1"	#5, 1-1/4"	4-Way	Down	25	KNP-6	1-10 Dial (Wide). Has 3/8" pipe stuffing box - nickel plated.

5300-400 (RX) SERIES

Note: Use of this control on alternating current (AC) will damage the switch. UL File # E12103.

- SPST – Break on temperature rise.
- Hermetically sealed reed switch provides durability and accuracy in the harshest environments.
- Rated for .67 amps at 5 VDC.
- Maximum ambient temperature 230°F (110°C).
- Maximum differential is 8°F.
- Precise and proven snap action mechanism.
- Standard type #1 mounting.
- Screw type terminals ensure electrical integrity.
- All RX models listed by UL, CSA, IEC, and AGA.
- Stem length 13/16".



5300-401

Uni-Line Part No.	Dial Temp. Range In °F	Cap. Length	Stem Flat	Bulb Size & Finish	Factory Stuffing Box	Model No.	Replaces O.E.M. Part No.	Replaces Robertshaw No.
5300-401	200 to 400	36"	Down	3/8" x 5-5/8" Nickel	1/4" Nickel	RX-1	Southbend #1182151, Anet's #P8905-03, Pitco #60125401, Dean #1204, Imperial #0319	KX-87, KX-299
5300-402	200 to 400	24"	Down	3/8" x 5-5/8" Nickel	3/8" Nickel	RX-10	Vulcan #411506-13, Star 2TY-9265	KX-396, RX-2
5300-403	200 to 375	24"	Down	3/8" x 5-5/8" Nickel	1/4" Nickel	RX-11	Frymaster #807-1692, Pitco #P5047587	KX-404, RX-3
5300-404	245 to 406	30"	Left	5/16" x 8-3/4"	None	RX-4	Keating #021081	KX-216, KX-439
5300-406	200 to 375	36"	Down	3/8" x 5-5/8" Nickel	3/8" Nickel	RX-6	Cecilware #L345A	KX-433
5300-408	200 to 400	48"	Up	1/4" x 9" Stainless Steel	3/8" Nickel	RX-8	Anet's #P8901-70	KX-287