



**IDENTIFICATION**

**AUXILIARY SWITCH**



TYPES "B", "E" & "F"  
HAS 3 AUXILIARY  
SWITCH TERMINALS



TYPES "A" & "J"  
HAS 2 AUXILIARY  
SWITCH TERMINALS

**AUXILIARY SWITCH DESCRIPTION**

Five types of auxiliary switches have been produced. Switch type is indicated by a letter designation in the Factory Model Number. Examples: EA3A-502-12 has a type "A" switch. SJ-170-36 has a type "J" switch.

SWITCH TYPE	SWITCH DESCRIPTION
A	SPST auxiliary switch rated for 25 Amp at 240 VAC. Switch is energized continuously in the dial "on" position. Does not cycle with the main contacts.
B	SPDT auxiliary switch rated for 25 Amp at 250 VAC. Bake contacts are energized continuously in the dial "on" position. Broil contact is made when dial is turned to "high" stop. Auxiliary switch contacts do not cycle with the main contacts.
E	SPDT auxiliary switch rated for 25 Amp at 250 VAC. Has full dial variable broil function when turned to the "high" stop position. Bake contacts are energized continuously in the dial "on" position. Broil contacts are made when dial is turned to "high" stop. Auxiliary switch contacts do not cycle with the main contacts.
F	SPDT auxiliary switch same as "E" designation, except switch is rated for 15 Amp at 240 VAC.
J	SPST auxiliary switch rated for 30 Amp at 240 VAC. Switch is energized continuously in the dial "on" position. Does not cycle with the main contacts.

**5300 CANADIAN DIRECT REPLACEMENT MODELS**

Uni-Line Part No.	Description	Temp. Range In °F	Cap. Length	Bulb Size	Dial Type	Mech. Differential	Stuffing Box Size	Comments & Applications
5300-C117	EAS-Direct Acting (Contacts open on temp. rise)	60 to 250	36"	3/8" x 4-7/16"	4-Way	8	3/8"	Steam Table
5300-C115	EAS-Direct Acting (Contacts open on temp. rise)	100 to 220	72"	3/8" x 5-3/4"	4-Way	8	3/8"	Steam Table
5300-C108	* EAS-Direct Acting (Contacts open on temp. rise)	100 to 450	66"	1/4" x 7-1/8" Tin Zinc	4-Way	12		Griddle
5300-C102	EAS-Direct Acting (Contacts open on temp. rise)	200 to 400	72"	5/16" x 7-9/16" Nickel	4-Way	8		Fryer
5300-C111	EAS-Direct Acting (Contacts open on temp. rise)	200 to 400	72"	5/16" x 7-9/16" Nickel	4-Way	8	1/4"	Fryer
5300-C121	EA17 - (Pilot Duty) Direct Acting (Contacts open on temp. rise)	200 to 400	48"	5/16" x 7-1/2" Nickel	4-Way	8	3/8"	Gold plated contacts. Dip sealed.