

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

**SECTION 1. IDENTIFICATION**

Product name : SPRAY ADHESIVE, 340 g

Product code : 890.910055

Other means of identification : No data available

**Manufacturer or supplier's details**

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd  
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : CANUTEC (24/7): +1 (613) 996-6666 or/ou \*666 (cellular/cellulaire)

E-mail address : prodsafe@wurth.ca

**Recommended use of the chemical and restrictions on use**

Recommended use : Adhesives

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ systemic toxicity - single exposure : Category 3

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Repeated exposure may cause skin dryness or cracking.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Propane	74-98-6	>= 10 - < 30
Acetone	67-64-1	>= 10 - < 30
Butane	106-97-8	>= 10 - < 30
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	>= 10 - < 30
Methyl acetate	79-20-9	>= 5 - < 10

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- |   |  |
|---|--|
| General advice  | : In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.   |
| If inhaled  | : If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.   |
| In case of skin contact                                     | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Get medical attention.<br>Wash clothing before reuse.<br>Thoroughly clean shoes before reuse. |
| In case of eye contact                                      | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.<br>If easy to do, remove contact lens, if worn.<br>Get medical attention.   |
| If swallowed  | : If swallowed, DO NOT induce vomiting.<br>Get medical attention if symptoms occur.<br>Rinse mouth thoroughly with water.  |
| Most important symptoms and effects, both acute and delayed | : Causes skin irritation.<br>Causes serious eye irritation.<br>May cause drowsiness or dizziness.<br>Prolonged or repeated contact may dry skin and cause irritation.  |
| Protection of first-aiders                                  | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.  |
| Notes to physician  | : Treat symptomatically and supportively.  |

**SECTION 5. FIRE-FIGHTING MEASURES**

- |                                       |   |
|---------------------------------------|---|
| Suitable extinguishing media          | : Water spray<br>Alcohol-resistant foam<br>Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical  |
| Unsuitable extinguishing media        | : High volume water jet   |
| Specific hazards during fire fighting | : Flash back possible over considerable distance.<br>Vapors may form explosive mixtures with air.<br>Exposure to combustion products may be a hazard to health. |

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapors/mists with a water spray jet.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapors or spray mist.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

Conditions for safe storage : Store locked up.  
Keep in a cool, well-ventilated place.  
Store in accordance with the particular national regulations.  
Do not pierce or burn, even after use.  
Keep cool. Protect from sunlight.

Materials to avoid : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures which in contact with water emit flammable gases  
Explosives

Recommended storage temperature : < 40 °C

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m <sup>3</sup>	CA QC OEL
Acetone	67-64-1	TWA	500 ppm 1,200 mg/m <sup>3</sup>	CA AB OEL
		STEL	750 ppm 1,800 mg/m <sup>3</sup>	CA AB OEL
		TWA	250 ppm	CA BC OEL

**SPRAY ADHESIVE, 340 g**

Version 3.2      Revision Date: 06/06/2019      SDS Number: 1228801-00002      Date of last issue: 12/07/2018  
 Date of first issue: 11/06/2013

		STEL	500 ppm	CA BC OEL
		TWAEV	500 ppm 1,190 mg/m <sup>3</sup>	CA QC OEL
		STEV	1,000 ppm 2,380 mg/m <sup>3</sup>	CA QC OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
Butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWAEV	800 ppm 1,900 mg/m <sup>3</sup>	CA QC OEL
		TWA	1,000 ppm	CA BC OEL
		STEL	1,000 ppm	ACGIH
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0	TWA (Mist)	5 mg/m <sup>3</sup>	CA AB OEL
		STEL (Mist)	10 mg/m <sup>3</sup>	CA AB OEL
		TWAEV (Mist)	5 mg/m <sup>3</sup>	CA QC OEL
		STEV (Mist)	10 mg/m <sup>3</sup>	CA QC OEL
Methyl acetate	79-20-9	TWA	200 ppm 606 mg/m <sup>3</sup>	CA AB OEL
		STEL	250 ppm 757 mg/m <sup>3</sup>	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	250 ppm	CA BC OEL
		TWAEV	200 ppm 606 mg/m <sup>3</sup>	CA QC OEL
		STEV	250 ppm 757 mg/m <sup>3</sup>	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

**Engineering measures**

: Minimize workplace exposure concentrations.  
 Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure potential  
 Use with local exhaust ventilation.  
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Rele-

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

vant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

Hand protection  
Material : Neoprene gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive atmospheres or flash fires is low.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Aerosol containing a liquefied gas
Propellant	: Propane, Butane
Color	: light yellow, clear
Odor	: solvent

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Heat of combustion	:	40.94 kJ/g
Particle size	:	Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	Not classified as a reactivity hazard.
------------	---	--



**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Propane:**

Acute inhalation toxicity	:	LC50 (Rat): > 800000 ppm Exposure time: 15 min Test atmosphere: gas
---------------------------	---	---

**Acetone:**

Acute oral toxicity	:	LD50 (Rat): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 76 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): 7,426 mg/kg

**Butane:**

Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	--

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.61 mg/l Exposure time: 4 h

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): &gt; 2,000 mg/kg

**Methyl acetate:**

Acute oral toxicity : LD50 (Rat): 6,482 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 49.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vaporAcute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation**Methyl acetate:**Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Acetone:**Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**Species : Rabbit  
Result : No eye irritation

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

**Methyl acetate:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 7 days
Method	:	OECD Test Guideline 405

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Acetone:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Propane:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 474 Result: negative

**Acetone:**

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative  Test Type: Bacterial reverse mutation assay (AMES) Result: negative  Test Type: Chromosome aberration test in vitro Result: negative
-----------------------	---	---

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapor)  
Method: OPPTS 870.5395  
Result: negative

**Methyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 474  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:****Acetone:**

Species : Mouse

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Application Route	: Skin contact
Exposure time	: 424 days
Result	: negative

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species	: Mouse
Application Route	: Skin contact
Exposure time	: 102 weeks
Result	: negative

**Methyl acetate:**

Species	: Rat
Application Route	: Inhalation
Exposure time	: 18 Months
Result	: negative
Remarks	: Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Propane:**

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
----------------------	--

Effects on fetal development	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: inhalation (gas) Method: OECD Test Guideline 422 Result: negative
------------------------------	--

**Acetone:**

Effects on fertility	: Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
----------------------	---

Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (vapor) Result: negative
------------------------------	--

**Butane:**

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat
----------------------	--

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative

**STOT-single exposure**

May cause drowsiness or dizziness.

**Components:****Propane:**

Assessment : May cause drowsiness or dizziness.

**Acetone:**

Assessment : May cause drowsiness or dizziness.

**Butane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**Methyl acetate:**

Assessment : May cause drowsiness or dizziness.

**STOT-repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Propane:**

Species : Rat  
NOAEL : 7.214 mg/l

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1,700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 8 Weeks

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rat  
NOAEL : > 20 mg/l  
Application Route : inhalation (vapor)  
Exposure time : 13 Weeks

**Methyl acetate:**

Species : Rat  
NOAEL : 1.057 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412

**Aspiration toxicity**

Not classified based on available information.

**Components:****Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Acetone:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5,540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8,800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): >= 79 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to microorganisms	:	EC50: 61,150 mg/l Exposure time: 30 min Method: ISO 8192

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 4.5 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials  NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOELR (Daphnia magna (Water flea)): 2.6 mg/l Exposure time: 21 d Method: OECD Test Guideline 211



**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

**Methyl acetate:**

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): 250 - 350 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,026.7 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): > 120 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- EC10 (Desmodesmus subspicatus (green algae)): > 120 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC10 (Pseudomonas putida): 1,830 mg/l  
Exposure time: 16 h

**Persistence and degradability****Components:****Propane:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Acetone:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

**Butane:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Methyl acetate:**

- Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 %  
Exposure time: 28 d

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

Method: OECD Test Guideline 301D

**Bioaccumulative potential****Components:****Acetone:**

Partition coefficient: n-octanol/water : log Pow: -0.27 - -0.23

**Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**Partition coefficient: n-octanol/water : log Pow: 4  
Remarks: Based on data from similar materials**Methyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 0.18

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**UN number : UN 1950  
Proper shipping name : AEROSOLS

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****TDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION**

**Volatile organic compounds (VOC) content** : CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products  
VOC content: 53.5 % / 388 g/l

**The ingredients of this product are reported in the following inventories:**

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

**SECTION 16. OTHER INFORMATION**
**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA BC OEL / STEL	:	short-term exposure limit
CA QC OEL / TWAEV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

**SPRAY ADHESIVE, 340 g**

Version	Revision Date:	SDS Number:	Date of last issue: 12/07/2018
3.2	06/06/2019	1228801-00002	Date of first issue: 11/06/2013

---

compile the Material Safety  
Data SheeteChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 06/06/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8